

PLASTERS AND FINISHES



AVAILABLE IN 20 KG PAILS - COVERAGE PER PAIL: 3 m² AT 5 mm THICKNESS

DESCRIPTION

Canapulino is a paste finish of lime putty (grassello di calce) aged 18 months and Canapulo Fine 0-6, with the addition of calcium carbonates (natural colour) or cocciopesto powder or coloured earths (colour to choice). The total absence of hydraulic binders and the high cellulose content maximise the breathability of the masonry and make Canapulino the ideal solution for the consolidation and completion of finishes, plasters and masonry. Desalinating and dehumidifying thanks to its high hygroscopic capacity, it is an excellent humidity regulator on new and existing walls, guarantees maximum healthiness and significantly improves the living comfort of interiors.

APPLICATIONS

Ready-to-use product, to be applied manually at a thickness of 5 to 10 mm. Before application, remove the existing plaster if deteriorated and make sure the substrate is free of friable parts. Apply a first coat of Canapulino as a rough coat (rinzafo) on the masonry and then apply in several coats up to the desired thickness, straighten with a screed and float.

Specific weight	1,110 kg/m ³
Water-vapour diffusion resistance - μ	4.5

NOTES

The TecnoCanapa technical office is available to provide support before, during and after the works.

The Company operates a constant process of improvement and modification of its products.

Technical data, packaging and pack sizes are therefore necessarily subject to change without notice. Customers may always check with the Company: technical data, documentation and samples.

For optimal use of the products it is recommended to follow faithfully the instructions given in the product technical data sheets and in the Biomattone® installation manual.