

PLASTERS AND FINISHES

MALTA FINE DI GRASSELLO E SABBIA



AVAILABLE IN 25 KG BAGS

DESCRIPTION

Malta Fine is a ready-to-use finishing plaster based on lime putty (grassetto di calce) and graded sands.

USE

Malta Fine is used as a civil-finish plaster on base-coat plasters of the **Intonaco di Calce Naturale** or **Bio Beton® 500 Venezia** type. For internal use only.

SUBSTRATE PREPARATION

The surface to be coated must be flat, level and free of dust and dirt. Any traces of oils, greases, waxes etc. must be removed beforehand. **Malta Fine** may be applied on a dry base-coat plaster after first dampening it.

APPLICATION

Apply with a metal trowel up to a maximum thickness of 3 mm. After application, dampen and finish with a small sponge float. It does not require mesh reinforcement.

STORAGE

If protected from frost it has no shelf-life limit.

TECHNICAL DATA

Specific weight	approx. 1,700 kg/m ³
Grain size	< 0.6 mm
Coverage	approx. 3-4 kg/m ²
Maximum application thickness	approx. 3 mm
Water-vapour diffusion resistance factor - EN 1015-19	$\mu \leq 9$ (measured value)
Capillary water absorption coefficient - EN 1015-18	W0
Thermal conductivity coefficient - EN 1745	$\lambda = 0.45$ W/m·K (tabulated value)
Class	GP-CSI-W0 according to standard UNI EN 998-1